

Ready-made round cable shielding sleeve



Ready-made round cable shielding sleeve 4700T

Ready-made round sleeve (EMI-screening sleeve) easy cable routing with high shielding performance

The ready-made round sleeve (EMI-screening sleeve) for round cables allows easy cable routing during assembly. The material is a highly conductive Amucor film offering full 360° protection against electromagnetic radiation. Shielding performance can even be improved using optional grouding connections.

For placing or curving round cables there is an ultra flexible solution with conductive textile with a self-adhesive, combining suberb mechanical and EMI-screening properties.

Ready-made round sleeves can be supplied in Amucor or in Conductive textile (fabric). The material provides high shielding performance. The ready-made round sleeve can be used for cables with large diameters.

Round cable connector shield

When your cable has a connector, it may be of importance for achieving the desired shielding effect to also shield the connector.

With earthing connection (on request)

The ready-made round sleeve can also be delivered with an earthing connection in any length and according to your drawing

Material options


- 4701T : Reinforced Amucor foil
- 4711T : Conductive fabric

Shielding performance (dB)

Frequency MHz	Mode	attenuation dB	
		Amucor	Conductive textile
1 MHz	E	121	115
10 MHz	Е	110	108
100 MHz	E	103	102
400 MHz	Е	98	92
1 GHz	Р	93	80
10 GHz	Р	90	87



Ready-made round cable shielding sleeve



Standard diameters

Diameter (mm)	Partnumber		
2	47xxx-2		
4	47xxx-4		
6	47xxx-6		
8	47xxx-8		
10	47xxx-10		
12	47xxx-12		
15	47xxx-15		
18	47xxx-18		
20	47xxx-20		
22	47xxx-22		
24	47xxx-24		
26	47xxx-26		
28	47xxx-28		
30	47xxx-30		
*Any other diameter available upon request, without tooling costs X=material options: Reinforced Amucor foil or Conductive fabric			

Part number Length (mm) Insulation Diameter (mm) Select an option: Select an option: Specify the diameter Specify the length 4701T : Reinforced I : Inside Amucor foil of the cable in mm per sleeve O: Outside (only 4711T : Conductive with amucor foil) Length fabric * Note: The **red** blocks are required Diameter